

NOVA TROLLEY


ONE YEAR WARRANTY

Approved ANSI B30.11


TECHNICAL SHEET

- Drop stops and bumpers
- Cast iron wheels
- Ball bearing
- Universal wheels ½ - 10T (I & H)
20T for I-beam only or H-beam only

1-5T 2 bolts + suspension plate
10T 3 bolts + suspension plate
20T 4 bolts + suspension plate



PLAIN



GEAR

TECHNICAL SPECS

MODEL		Dimensions in								Plain	Gear* 10' chain
		Cap. Tons	G Head- room	Beam** min. Height	Width (flange)**		H Wheel Tread dia	L Tread Width	Radius of curve min.**		
Plain	Gear*				Min.	Max.				lb	
NPT1/2T	NGT1/2T	1/2	4 7/16	3	2 1/2	6	2 1/4	1	36	16	27
NPT1T	NGT1T	1	5 1/8	4	2 3/4	6	2 15/16	1 1/8	40	28	38
NPT1.5T	NGT1.5T	1 1/2	5 3/4	5	3 1/8	6 5/8	3 5/16	1 1/8	48	42	51
NPT2T	NGT2T	2	6	5	3 1/8	6 3/4	3 1/2	1 5/16	49	46	55
NPT3T	NGT3T	3	7 1/4	5	3 5/8	8 1/2	4 5/16	1 7/16	60	81	93
NPT5T	NGT5T	5	8 5/8	6	4 1/8	8 1/2	4 13/16	1 3/4	79	118	133
NPT10T	NGT10T	10	10 3/4	8	4 1/2	8 1/2	5 15/16	1 7/8	87	213	226
NPT20T	NGT20T	20	12	10	7	10	7 3/4	2 7/8	111	513	536

Specify beam height & width or height & lb per ft

* When used w/electric hoist, hand chain wheel extension required & hoist must be parallel to beam

** May vary depending on the size of the beam

