

ADJUSTABLE PUSH TROLLEY

SERIES **XT**

THE MANUAL ADJUSTABLE PUSH TROLLEY FROM VULCAN'S XT SERIES:

Perfectly combines design,
construction and ease of use

1T to 5T capacities

Unmatched value for the price

2-year warranty

ANSI B30.11-certified

Complete nameplate with serial number

150% test load

Testing and inspection
certificate included



Fast and easy installation

- Installation does not require any tools

Safe

- A unique latch system prevents loosening of the adjustment screw

Maintenance-free

- Sealed ball bearings with permanent lubrication

Corrosion-resistant

- High-resistance powder coat paint
- Zinc-plated mechanical parts

Compatible

- Wheels compatible with most beam profiles



I and S beam
TAPERED



H and W beam
FLAT

ADJUSTABLE PUSH TROLLEY SERIES XT

MODEL	Capacity	Safe working load	Test load 150%	Width (flange)		Curve radius min.*	Net weight
	Tons (MT)			Min.	Max.		
		lb	lb	in.		ft	lb
XTAT1T	1	2200	3300	2,5	8	3,28	25
XTAT2T	2	4400	6600	3	8,25	3,61	38
XTAT3T	3	6600	9900	3	8,25	4,26	57
XTAT5T	5	11 000	16 500	4	12	4,60	102

* May vary depending on beam dimensions

MODEL	Dimensions						
	A	B	C	D (min. - max.)	E	F	G
	in.						
XTAT1T	13,98	9,53	0,88	5,75~7,22	2,75	0,75	3,75
XTAT2T	14,71	11,06	0,88	6,06~7,22	2,13	0,83	4,25
XTAT3T	14,71	12,91	0,97	6,35~7,97	2,83	1,13	5,06
XTAT5T	18,5	14,84	1,11	8,81~10,61	3,38	3,38	5,75

