

PUSH TROLLEY

SERIES **XT**

VULCAN'S XT SERIES PUSH TROLLEY:

Reliability and safety under any
circumstances to move a load when no
electric supply is needed or available

1/2T to 5T capacities

2-year warranty

ANSI B30.11 certified

Complete nameplate with serial number

150% test load

Testing and inspection
certificate included

NEW!



Maintenance-free

- Sealed ball bearings with permanent lubrication

Weatherproof

- High-resistance powder coat paint
- Zinc-plated mechanical parts

Easy to handle

- Superior handling for use on curved beams that require a low turning radius

Compatible

- Wheels compatible with most beam profiles



I and S beam
TAPERED



H and W beam
FLAT

PUSH TROLLEY SERIES XT

MODEL	Capacity	Safe working load	Test load 150%	Width (flange)		Curve radius min.*	Net weight
	Tons (MT)	lb	lb	Min.	Max.	ft	lb
				in.			
XPT0,5T	0,5	1 100	1 650	2,5	6,0	2,95	20
XPT1T	1	2 200	3 300	2,5	8,25	3,28	32
XPT2T	2	4 400	6 600	3,5	8,25	3,60	50
XPT3T	3	6 600	9 900	4,0	12,0	4,26	82
XPT5T	5	11 000	16 500	4,25	12,0	4,59	123

* May vary depending on beam dimensions

MODEL	Dimensions						
	A	B	C	D	E	F	G
	ft						
XPT0,5T	9,75	8,50	7,67	4,33	2,25	1,13	3,25
XPT1T	12,69	10,24	9,41	5,31	2,88	1,13	4,00
XPT2T	13,19	11,81	11,26	6,34	3,63	1,50	4,75
XPT3T	14,31	13,58	13,23	7,28	4,25	1,50	5,63
XPT5T	15,07	15,55	15,47	8,66	4,75	1,50	6,50

